

1. Identification of the substance/mixture and of the company/undertaking

Product Name: PolyWood[™] 3D Printing Filament
CAS No.: See Section 3
Identified Uses: for fused deposition modeling (FDM) or fused filament fabrication (FFF) based additive manufacturing and 3D printing processes

Manufacturer: JF Polymers (Suzhou) Co. Ltd. Address: 11 Sihai Rd, Unit 2, Suite 502, Changshu, Jiangsu Province 215513, China Tel/Fax: +86-512-52096516 / +86-512-52096512

Emergency telephone number: +86-512-52096516; or call LOCAL POISON CONTROL CENTER

2. Hazards identification

Emergency Overview

Not likely to be an irritant in the solid form. Burning produces obnoxious and toxic fumes. Avoid prolonged contact with skin and contact with eyes. Not likely to form a dust in the solid filament form.

Potential Acute Health Effects

Inhalation: Not likely to form an inhalable dust in the solid filament form and for the intended use. Aerosols generated during printing may cause shortness of breath, tightness of the chest, a sore throat and cough.

Eye: Direct contact with eyes may cause irritation.

Skin: May cause slight skin irritation.

Ingestion: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Potential Chronic Health Effects

Carcinogenic Effects: No known carcinogenic effects Mutagenic Effects: No known mutagenic effects Teratogenic Effects: No known teratogenic effects Developmental Toxicity: No known developmental toxicity

3. Composition/information on ingredients

Chemical Name	CAS No.	Weight %	Exposure Limits
Poly(lactic acid) resin	9051-89-2	> 90%	None

4. First aid measures

Inhalation: Move to fresh air and keep at rest in a position comfortable for breathing. Call a physician immediately if irritation persists.

Skin contact: Rinse immediately with plenty of water. If skin irritation persists, call a physician. Cool skin rapidly with cold water after contact with hot polymer.

Eye contact: Rinse immediately with plenty of water. Call a physician immediately.

Ingestion: Drink water as a precaution. Never give anything by mouth to an unconscious person. Do not induce omitting without medical advice. Call a physician immediately.

Notes for the doctor: Treat symptomatically.

5. Fire-fighting measures

General Information: As in any fire, wear self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Suitable Extinguishing Agents: Foam. Water. Carbon dioxide (CO₂). Dry chemical. Alcohol resistant foams are preferred if available. General-purpose synthetic foams (including AFFF) or protein foams may function, but much less effectively.

Products of Combustion: Burning produces obnoxious and toxic fumes, aldehydes, carbon monoxide (CO), carbon dioxide (CO₂), low molecular weight hydrocabons.

Special Fire Fighting Procedures: Firefighters should wear self-contained breathing apparatus and full fire-fighting turn-out gear (bunker gear). Keep personnel removed and upwind of fire. Water should be used to keep fire-exposed containers cool.

Special Remarks on Fire and Explosion Hazards: Toxic gases/vapors/fumes may emit in a fire.

6. Accidental release measures

General: Wear gloves when handling hot melt of the material.

Environmental precautions: Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system.

Methods and material for containment and cleaning up: Shovel into suitable container for disposal.

7. Handling and storage

Precautions: No special precautions required.

Handling: Wear gloves when handling molten material. Low hazard for usual industrial or commercial handling.

Storage: Store in cool place. Keep at temperatures below 122F (50 °C). No special restrictions on storage with other products.

8. Exposure controls/personal protection

JF Polymers (Suzhou) Co. Ltd. All rights reserved.



Ventilation protection: Provide good ventilation during 3D printing processes.
Skin protection: avoid direct contact to the hot melt of material or wear gloves.
Eye and face protection: Safety glasses if necessary.
General: Wear protective clothing to prevent contact with hot melt materials.

9. Physical and chemical properties

Appearance: Filament, Solid Color: Various Odour: Odorless pH: Not applicable Melting point: > 140 °C Boiling point: Not applicable Density: < 1 g/cm³ Vapor pressure: Not applicable Partition coefficient (n -octanol/water): Not applicable Solubility(ies): Not determined Flash point: Not determined Auto-ignition temperature: Not determined

10. Stability and Reactivity

Stability: Stable under recommended storage conditions
Polymerization: Not applicable
Dangerous Decomposition Products: Burning produces obnoxious and toxic fumes. Aldehydes.
Carbon monoxide (CO). carbon dioxide (CO2). low molecular weight hydrocarbons.
Conditions to avoid: Temperatures above 446F (230 °C).
Materials to avoid: Oxidizing agents. Strong bases.

11. Toxicological information

Routes of entry: N.A. Acute toxicity: Not likely to cause targeted organ effects or skin allergic reactions.

12. Ecological information

Mobility: No data available Bioaccumulation: The main resin is biodegradable. Ecotoxicity effects: Data not available.

13. Disposal considerations



Waste Disposal Methods: In accordance with local and national regulations. Do not contaminate ponds, waterways or ditches with chemical or used container. Contact manufacturer if needed.

14. Transport information

No a DOT controlled material (United States)

Proper Shipping Name: Not regulated
Hazzard Class: Not regulated
UN. NO.: Not regulated
Packing Group: Not regulated
IMDG EMS: Not regulated

15. Regulatory information

European/International Regulations

This product is on the European Inventory of Existing Commercial Chemical Substances.

European Labeling in Accordance with EC Directives

Hazard Symbols: N/A Risk phrases: N/A Safety phrases: N/A

HMIS (U.S.A.): Health Hazard: 0 Fire Hazard: 1 Reactivity: 0 Personal Protection:

National Fire Protection Association(U.S.A.): Health: 0 Flammability: 1 Reactivity: 0 Specific Hazard:

Federal and State Regulations:

TSCA 8(b) inventory: Listed

Canada–WHMIS:

Not controlled

For details regulations you should contact the appropriate agency in your country.

JF Polymers (Suzhou) Co. Ltd. All rights reserved.



16. Other information

Revision information Date of this revision: June 14 2014

Declare to reader

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. This shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.